

Zaristo 125G(TR70806)

Updated : September 1, 2015

SDS No. : MS-7080601-00

SECTION 1 IDENTIFICATION

MANUFACTURER TAIYO INK MFG. CO.,LTD. TEL 81-493-62-7277
 388 Ohkura, Ranzan-machi, Hiki-gun FAX 81-493-62-7962
 Saitama, 355-0222 JAPAN

DISTRIBUTOR

EMERGENCY CONTACT TEL 81-493-62-7277 FAX 81-493-62-7962

SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS	CAS No.	CONTENTS (%)	OSHA (PEL)	ACGIH (TLV)
Bisphenol A-(epichlorhydrin);Epoxy resin(Mw \leq 700)	25068-38-6	< 4%	N. A.	N. A.
Epoxy resin(Mw \leq 700)	Trade secret	< 4%	N. A.	N. A.
Epoxy compound (MW \leq 700)	Trade secret	< 21%	N. A.	N. A.
Silica, amorphous	7631-86-9	< 60%	N. A.	dustTLV10mg/m3

SECTION 3 HAZARDS IDENTIFICATION

INHALATION : Highly concentrated vapor irritates nose, throat and lungs.
 May cause headache and dizziness.

EYE CONTACT : Slight irritation

SKIN CONTACT : Sensitization

INGESTION : Harmful, if swallowed.

SECTION 4 FIRST AID MEASURES

SKIN CONTACT : Wash with plenty of running water using a mild soap. Do not use
 organic solvents.

EYE CONTACT : Rinse immediately with clean water for at least 15 minutes.
 If irritation persists, seek medical attention.

INHALATION : Immediately carry the victim to a place where fresh air is available.
 If irritation persists, treat with oxygen and seek medical attention.

INGESTION : Obtain medical advice immediately. It is not recommended that
 vomiting be induced except on medical advice.

SECTION 5

FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA	: Carbon dioxide, foam, powder.
UNSUITABLE EXTINGUISHING MEDIA	: Water jet.
EXPOSURE HAZARDS	: Burning may release oxides of carbon, nitrogen, sulphur and other toxic gases or vapors. Do not release chemically contaminated water into drains or surface waters. Dispose of contaminated waters and soil according to local regulations.
PROTECTIVE EQUIPMENT FOR FIREFIGHTERS MEASURES	: Use full protective clothing and self-contained breathing apparatus. : Promptly move transferable containers to another safety area. Check the speed and spread of fire. Extinguish the fire with suitable extinguisher from the windward side.

SECTION 6

ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTION	: Avoid ignition sources. Avoid contact with skin, eyes and clothing. Avoid inhaling vapor.
ENVIRONMENTAL PRECAUTIONS METHODS FOR CLEANING	: Prevent contamination of soil, drains and surface waters : Scoop up or absorb into combustible material, wipe out a stain in use organic solvents. Dispose in accordance with local regulations.

SECTION 7

HANDLING AND STORAGE

HANDLING	: Handle with care. Avoid ignition sources. Ensure good ventilation and local exhaust. Do not smoke at the workplace.
STORAGE	: Store in the original container at less than -15°C. Avoid direct exposure to UV and sunlights.

SECTION 8

EXPOSURE CONTROLS/PERSONAL PROTECTION

People who know they are chemically sensitive, should avoid contact with this product.	
TECHNICAL PROTECTIVE MEASURES	: No special safety measures required.
EXPOSURE CONTROL LIMITS	: (See PEL and TLV values shown in section 2)
RESPIRATORY PROTECTION	: Wear suitable mask to avoid inhalation of vapor.
HAND PROTECTION	: Wear chemical resistant gloves.
EYE PROTECTION	: Wear safety glasses.
SKIN PROTECTION	: Wear suitable protective working cloths.

SECTION 9

PHYSICAL AND CHEMICAL PROPERTIES

COLOR	: Green		
FORM	: Film ; Carrier film(PET) / Resin / Cover film(PP)		
BOILING POINT	: *156°C (760mmHg)	FLASH POINT	: N.A. (gelation)
VAPOR PRESSURE	: * 0.34mmHg (20°C)	VAPOR DENSITY	: * 3.40 (Air=1)
SOLUBILITY IN WATER	: N.E.	ODOR	: Mild odor
		SPECIFIC GRAVITY	: N.E.

SECTION 10

STABILITY AND REACTIVITY

STABILITY : Stable
CONDITIONS TO AVOID : Heat and sunlight.
MATERIALS TO AVOID : Strong acids, strong bases, peroxides and strong oxidizing agents.
HAZARDOUS DECOMPOSITION PRODUCTS : Burning may release oxides of carbon, nitrogen, sulphur and other toxic gases or vapors.

SECTION 11

TOXICOLOGICAL INFORMATION

PRIMARY ROUTE(S) OF ENTRY

DERMAL INHALATION INGESTION

TOXICITY STUDIES : Toxicity studies have not been carried out on this product. Toxicity information available for the ingredients listed in section 2 is given below.

HEALTH HAZARDS

ACUTE INGESTION TOXICITY : N.E.
ACUTE SKIN IRRITATION : Epoxy compound (MW \leq 700) PII= 5.9
MUTAGENICITY : Bisphenol A-(epichlorhydrin); Epoxy resin (Mw \leq 700)
Epoxy resin (Mw \leq 700)
Epoxy compound (MW \leq 700)
is suspected to have a mutagenicity

CARCINOGENICITY

NTP IARC OSHA NOT LISTED

SYMPTOMS OF OVER EXPOSURE

INHALATION : Slight irritation to respiratory tract. Highly concentrated vapor may cause headaches, dizziness, and nausea.
EYES : Slight irritation
SKIN : Sensitization
INGESTION : Expected to have a low order of toxicity.

SECTION 12

ECOLOGICAL INFORMATION

ACUTE FISH TOXICITY : Ecological data are not available
BIODEGRADABILITY : U. K.

SECTION 13

DISPOSAL CONSIDERATIONS

Incineration or landfill in accordance with local regulations.

SECTION 14

TRANSPORT INFORMATION

IMDG-CODE : Free
IATA : Free
UN : Free
FLASH POINT : N. A. (gelation)

SECTION 15REGULATORY INFORMATION

EEC LABELING : Xn=Harmful

Xi=Irritant

RISK PHRASES : R43 - May cause sensitization by skin contact.

SAFETY PHRASES : S37/39 - Wear suitable gloves and eye/face protection.
S28 - After contact with skin, wash immediately with plenty of
water and soap.TSCA : on TSCA on LVE NOT LISTEDEINECS : on EINECS on ELINCS NOT LISTED

SECTION 16

OTHER INFORMATION

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation. The information contained herein is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It should not therefore be construed as guaranteeing specific properties.
It may not be valid for this material, if used in combination with any other materials.

Data provided in Section 11,12 and 15 are quoted from raw materials MSDSs.

Please kindly contact to our local sales office/distributor in case if you plan to export this product before use.