PSR-4000 FLX101

Updated : November 27, 2014

MSDS No. : MS-00170401-07

SECTION 1 IDENTIFICATION

MANUFACTURER TAIYO INK MFG. CO., LTD. TEL 81-493-61-2724

900 Hirasawa, Ranzan-machi, Hiki-gun FAX 81-493-61-2824

Saitama, 355-0215 JAPAN

DISTRIBUTOR

EMERGENCY CONTACT TEL 81-493-61-2724 FAX 81-493-61-2824

SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS CAS No. CONTENTS (%) OSHA ACGIH (PEL) (TLV)Solvent naphtha (petroleum), Heavy arom. < 11% N.A. 64742-94-5 N.A. Naphthalene (Carc. Cat. 3; R40) 91-20-3 < 1% 10ppm10ppm Morpholine derivative Trade secret < N. A. N. A. Silica, amorphous Trade secret < 4% N.A. dustTLV10mg/m3

SECTION 3 HAZARDS IDENTIFICATION

INHALATION : Highly concentrated vapor irritates nose, throat and lungs.

May cause headache and dizziness.

EYE CONTACT : Slight irritation SKIN CONTACT : Slight irritation INGESTION : Harmful, if swallowed.

SECTION 4 FIRST AID MEASURES

SKIN CONTACT : Wash with plenty of running water using a mild soap. Do not use

organic solvents.

EYE CONTACT : Rinse immediately with clean water for at least 15 minutes.

If irritation persists, seek medical attention.

INHALATION : Immediately carry the victim to a place where fresh air is available.

If irritation persists, treat with oxygen and seek medical attention.

INGESTION : Obtain medical advice immediately. It is not recommended that

vomiting be induced except on medical advice.

SECTION 5 FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA : Carbon dioxide, foam, powder. UNSUITABLE EXITINGUISHING MEDIA: Water spray and water jet.

EXPOSURE HAZARDS : Burning may release oxides of carbon, nitrogen,

> sulphur and other toxic gases or vapors. Do not release chemically contaminated water into drains or surface waters. Dispose of contaminated waters and soil

according to local regulations.

PROTECTIVE EQUIPMENT : Use full protective clothing and self-contained breathing apparatus.

FOR FIREFIGHTERS

MEASURES : Promptly move transferable containers to another

> safety area. Check the speed and spread of fire. Extinguish the fire with suitable

SECTION 6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTION : Avoid ignition sources. Avoid contact with skin, eyes

and clothing. Avoid inhalating vapor.

ENVIRONMENTAL PRECAUTIONS : Prevent contamination of soil, drains and surface waters

: Scoop up or absorb into combustible material, wipe out a stain in use organic solvents. Dispose in accordance

with local regulations.

SECTION 7 HANDLING AND STORAGE

HANDLING : Handle with care. Avoid ignition sources. Ensure good

ventilation and local exhaust. Do not smoke at the

workplace.

STORAGE : Store in the original sealed container at less than

 $20\,^{\circ}\!\text{C}_{\,\cdot}$. Avoid direct exposure to UV and sunlights.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

People who know they are chemically sensitive, should avoid contact with this

product.

METHODS FOR CLEANING

TECHNICAL PROTECTIVE MEASURES : No special safety measures required.

EXPOSURE CONTROL LIMITS : (See PEL and TLV values shown in section 2)
RESPIRATORY PROTECTION : Wear suitable mask to avoid inhalation of vapor.

HAND PROTECTION : Wear chemical resistant gloves.

EYE PROTECTION : Wear safety glasses.

SKIN PROTECTION : Wear suitable protective working cloths.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT : $*190^{\circ}$ C (760mmHg) COLOR : Green FLASH POINT : 79.0° C (Seta C.C.) FORM : Paste

VAPOR PRESSURE : * 2.00mmHg (38° C) VAPOR DENSITY : * 6.12 (Air=1)

SOLUBILITY IN WATER : *< 22.7wt% ODOR : Mild odor

SPECIFIC GRAVITY : N.E.

*Data of the organic solvents or monomers contained in this product is quoted.

SECTION 10 STABILITY AND REACTIVITY

STABILITY : Stable

CONDITIONS TO AVOID : Heat and sunlight.

MATERIALS TO AVOID : Strong acids, strong bases, peroxids and strong

oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS : Burning may release oxides of carbon, nitrogen,

sulphur and other toxic gases or vapors.

SECTION 11 TOXICOLOGICAL INFORMATION

PRIMARY ROUTE(S) OF ENTRY

■ DERMAL ■ INHALATION □ INGESTION

TOXICITY STUDIES : Toxicity studies have not been carried out on this

product. Toxicity information available for the ingredients listed in section 2 is given below.

HEALTH HAZARDS

ACUTE INGESTION TOXICITY : N.E.

ACUTE SKIN IRRITATION : Slightly irritant

MUTAGENICITY : NONE

CARCINOGENICITY

 $\blacksquare \ \, \mathsf{NTP} \qquad \qquad \blacksquare \ \, \mathsf{IARC} \qquad \qquad \square \ \, \mathsf{OSHA} \qquad \blacksquare \ \, \mathsf{EU} \qquad \qquad \square \ \, \mathsf{NOT} \ \, \mathsf{LISTED}$ Naphthalene is reported to be possibly carcinogenic based on its IARC, NTP, and EU

classification.

SYMPTOMS OF OVER EXPOSURE

INHALATION : Slight irritation to respiratory tract. Highly

concentrated vapor may cause headaches, dizziness,

and nausea.

EYES : Slight irritation SKIN : Slight irritation

INGESTION : Expected to have a low order of toxicity.

SECTION 12 ECOLOGICAL INFORMATION

ACUTE FISH TOXICITY : Ecological data are not available

BIODEGRADABILITY : U.K.

SECTION 13 DISPOSAL CONSIDERATIONS

Incineration or landfill in accordance with local regulations.

SECTION 14 TRANSPORT INFORMATION

IMDG-CODE : Free
IATA : Free
UN : Free

FLASH POINT : 79.0° C (Seta C.C.)

SECTION 15	REGULATORY INFORMATION
EEC LABELING	: Xn=Harmful
	N = Dangerous for the environment
RISK PHRASES	 R40 - Limited evidence of a carcinogenic effect. R65 - Harmful:may cause lung damage if swallowed. R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
SAFETY PHRASES	 S24 - Avoid contact with skin. S36/37 - Wear suitable protective clothing and gloves. S23 - Do not breathe vapour. S46 - If swallowed, seek medical advice immediately and show this container or label. S61 - Avoid release to the environment. Refer to special instructions/Safety data sheets. S60 - This material and its container must be disposed of as hazardous waste.
TSCA	: □on TSCA □on LVE ■NOT LISTED *This product contains a substance listed on the TSCA inventory and in addition is subject to the Significant New Use Rule(SNUR) found in 40CFR721.9664
EINECS	: ■on EINECS ■on ELINCS □NOT LISTED

SECTION 16 OTHER INFORMATION

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation. The information contained herein is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It should not therefore be construed as guaranteeing specific properties.

It may not be valid for this material, if used in combination with any other materials.

Data provided in Section 11,12 and 15 are quoted from raw materials MSDSs.

Please kindly contact to our local sales office/distributor in case if you plan to export this product before use.

CA - 40 FLX 101

Updated : November 27, 2014

MSDS No. : MS-00170501-01

SECTION 1 IDENTIFICATION

MANUFACTURER TAIYO INK MFG. CO., LTD. TEL 81-493-61-2724

900 Hirasawa, Ranzan-machi, Hiki-gun FAX 81-493-61-2824

Saitama, 355-0215 JAPAN

DISTRIBUTOR

EMERGENCY CONTACT TEL 81-493-61-2724 FAX 81-493-61-2824

SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS

> INGREDIENTS CAS No. CONTENTS (%) OSHA ACGIH

(PEL) (TLV)

Epoxy resin (MW ≤ 700 , Carc.cat.3; R40, R43)

85954-11-6 < 33% N. A. N.A.

Silica, amorphous Trade secret < 3% N.A. dustTLV10mg/m3

SECTION 3 HAZARDS IDENTIFICATION

INHALATION : Highly concentrated vapor irritates nose, throat and lungs.

May cause headache and dizziness.

EYE CONTACT : Slight irritation SKIN CONTACT : Sensitization

INGESTION : Harmful, if swallowed.

SECTION 4 FIRST AID MEASURES

SKIN CONTACT : Wash with plenty of running water using a mild soap. Do not use

organic solvents.

EYE CONTACT : Rinse immediately with clean water for at least 15 minutes.

If irritation persists, seek medical attention.

INHALATION : Immediately carry the victim to a place where fresh air is available.

If irritation persists, treat with oxygen and seek medical attention.

INGESTION : Obtain medical advice immediately. It is not recommended that

vomiting be induced except on medical advice.

SECTION 5 FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA : Carbon dioxide, foam, powder. UNSUITABLE EXITINGUISHING MEDIA: Water spray and water jet.

EXPOSURE HAZARDS : Burning may release oxides of carbon, nitrogen,

sulphur and other toxic gases or vapors. Do not release chemically contaminated water into drains or surface waters. Dispose of contaminated waters and soil

according to local regulations.

PROTECTIVE EQUIPMENT : Use full protective clothing and self-contained

FOR FIREFIGHTERS breathing apparatus.

MEASURES : Promptly move transferable containers to another

> safety area. Check the speed and spread of fire. Extinguish the fire with suitable

extinguisher from the windward side.

SECTION 6

ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTION

METHODS FOR CLEANING

: Avoid ignition sources. Avoid contact with skin, eyes

and clothing. Avoid inhalating vapor.

ENVIRONMENTAL PRECAUTIONS

: Prevent contamination of soil, drains and surface waters

: Scoop up or absorb into combustible material, wipe out

a stain in use organic solvents. Dispose in accordance

with local regulations.

SECTION 7

HANDLING AND STORAGE

HANDLING

: Handle with care. Avoid ignition sources. Ensure good

ventilation and local exhaust. Do not smoke at the

workplace.

STORAGE

: Store in the original sealed container at less than

 $20\,^{\circ}\!\text{C}$. Avoid direct exposure to UV and sunlights.

SECTION 8

EXPOSURE CONTROLS/PERSONAL PROTECTION

People who know they are chemically sensitive, should avoid contact with this

product.

TECHNICAL PROTECTIVE MEASURES : No special safety measures required.

EXPOSURE CONTROL LIMITS : (See PEL and TLV values shown in section 2)

RESPIRATORY PROTECTION : Wear suitable mask to avoid inhalation of vapor.

HAND PROTECTION : Wear chemical resistant gloves.

EYE PROTECTION : Wear safety glasses.

SKIN PROTECTION : Wear suitable protective working cloths.

SECTION 9

PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT : *191°C (760mmHg) COLOR : White FLASH POINT : 134.0℃ (Cleveland O.C.)FORM : Paste

VAPOR PRESSURE : * 2.00mmHg(38℃) VAPOR DENSITY : * 6.12 (Air=1)

SOLUBILITY IN WATER : *< 13.3wt% ODOR : Mild odor

SPECIFIC GRAVITY: N.E.

*Data of the organic solvents or monomers contained in this product is quoted.

SECTION 10

STABILITY AND REACTIVITY

STABILITY

: Stable

CONDITIONS TO AVOID

: Heat and sunlight.

MATERIALS TO AVOID

: Strong acids, strong bases, peroxids and strong

oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Burning may release oxides of carbon, nitrogen,

sulphur and other toxic gases or vapors.

SECTION 11 TOXICOLOGICAL INFORMATION

PRIMARY ROUTE(S) OF ENTRY

■ DERMAL ■ INHALATION □ INGESTION

TOXICITY STUDIES : Toxicity studies have not been carried out on this

product. Toxicity information available for the ingredients listed in section 2 is given below.

HEALTH HAZARDS

ACUTE INGESTION TOXICITY : N.E.

ACUTE SKIN IRRITATION : Slightly irritant

 $\texttt{MUTAGENICITY} \qquad : \texttt{Epoxy resin} \, (\texttt{MW} \leqq 700, \texttt{Carc.cat.3}; \texttt{R40}, \texttt{R43})$

is suspected to have a mutagenicity

CARCINOGENICITY

■NTP □ IARC □ OSHA ■ NOT LISTED

SYMPTOMS OF OVER EXPOSURE

INHALATION : Slight irritation to respiratory tract. Highly

concentrated vapor may cause headaches, dizziness,

and nausea.

EYES : Slight irritation SKIN : Sensitization

INGESTION : Expected to have a low order of toxicity.

SECTION 12 ECOLOGICAL INFORMATION

 $\begin{tabular}{ll} ACUTE FISH TOXICITY : Ecological data are not available \\ \end{tabular}$

BIODEGRADABILITY : U.K.

SECTION 13 DISPOSAL CONSIDERATIONS

Incineration or landfill in accordance with local regulations.

SECTION 14 TRANSPORT INFORMATION

FLASH POINT : 134.0°C (Cleveland O.C.)

SECTION 15 REGULATORY INFORMATION

EEC LABELING : Xn=Harmful

RISK PHRASES : R40 - Limited evidence of a carcinogenic effect.

R43 - May cause sensitization by skin contact.

SAFETY PHRASES : S36/37 - Wear suitable protective clothing and gloves.

S22 - Do not breathe dust.

TSCA : \square on TSCA \square on LVE \square NOT LISTED EINECS : \square on EINECS \square on ELINCS \square NOT LISTED

SECTION 16 OTHER INFORMATION

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation. The information contained herein is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It should not therefore be construed as guaranteeing specific properties.

It may not be valid for this material, if used in combination with any other materials.

Data provided in Section 11,12 and 15 are quoted from raw materials MSDSs.

Please kindly contact to our local sales office/distributor in case if you plan to export this product before use.