page 1/4

P S R - 8 0 0	AUS SR1	Updat SDS N	ed : January o. : MS-0025	13, 2016 4301-03	
SECTION 1	IDENTIFICATION				
MANUFACTURER	TAIYO INK MFG. CO., LTD.TEL 81-493-61-2724900 Hirasawa, Ranzan-machi, Hiki-gunFAX 81-493-61-2824Saitama, 355-0215 JAPANFAX 81-493-61-2824				
DISTRIBUTOR					
EMERGENCY CONTACT	T TEL 81-493-61-2724 FAX	81-493-	61-2824		
SECTION 2	COMPOSITION/INFORMATION ON ING	GREDIENTS			
ING	REDIENTS CAS No. CON	TENTS (%)	OSHA (PEL)	ACGIH (TLV)	
Barium Sulfate Silica,amorphous	7727-43-7 < 7631-86-9 < 700, Carc.cat.3;R40,R43) 85954-11-6 <	<pre>3% 20% 10% 5% 3%</pre>	20mppcf dust 15mg/m3 N.A. N.A. N.A.	2mg/m3(R) 10mg/m3 dustTLV10mg/m3 N. A. N. A.	
SECTION 3	HAZARDS IDENTIFICATION	I			
EYE CONTACT : SKIN CONTACT :	Highly concentrated vapor irritat May cause headache and dizziness. Slight irritation Sensitization Harmful, if swallowed.		throat and lu	ngs.	
SECTION 4	FIRST AID MEASURES				
EYE CONTACT : INHALATION :	Wash with plenty of running water organic solvents. Rinse immediately with clean water If irritation persists, seek medi Immediately carry the victim to a If irritation persists, treat wit Obtain medical advice immediately vomiting be induced except on med	er for at cal atte place w h oxygen r. It is	least 15 minu ntion. here fresh air and seek medi not recommend	tes. is available. cal attention.	

SECTION 5 FI	RE-FIGHTING MEASURES		
SUITABLE EXTINGUISHING MEDIA UNSUITABLE EXITINGUISHING MEDIA EXPOSURE HAZARDS	 Carbon dioxide, foam, powder. Water jet. Burning may release oxides of carbon, nitrogen, sulphur and other toxic gases or vapors. Do not release chemically contaminated water into drains or 		
PROTECTIVE EQUIPMENT FOR FIREFIGHTERS MEASURES	 surface waters. Dispose of contaminated water into drains of according to local regulations. Use full protective clothing and self-contained breathing apparatus. Promptly move transferable containers to another safety area. Check the speed and spread of fire. Extinguish the fire with suitable extinguisher from the windward side. 		
SECTION 6 ACCID	DENTAL RELEASE MEASURES		
PERSONAL PRECAUTION ENVIRONMENTAL PRECAUTIONS	 Avoid ignition sources. Avoid contact with skin, eyes and clothing. Avoid inhalating vapor. Prevent contamination of soil, drains and surface waters 		
METHODS FOR CLEANING	: Scoop up or absorb into combustible material,wipe out a stain in use organic solvents. Dispose in accordance with local regulations.		
SECTION 7 HA	NDLING AND STORAGE		
HANDLING	: Handle with care. Avoid ignition sources. Ensure good ventilation and local exhaust. Do not smoke at the workplace.		
STORAGE	 Store in the sealed container at less than -15℃. Avoid direct exposure to UV and sunlights. 		
SECTION 8 EXPOSURE	CONTROLS/PERSONAL PROTECTION		
product.	 cally sensitive, should avoid contact with this No special safety measures required. (See PEL and TLV values shown in section 2) Wear suitable mask to avoid inhalation of vapor. Wear chemical resistant gloves. Wear safety glasses. Wear suitable protective working cloths. 		
SECTION 9 PHYSIC	CAL AND CHEMICAL PROPERTIES		
COLOR : Green FORM : Film ; C BOILING POINT : N.E. VAPOR PRESSURE : N.E.	Carierfilm(PET) / Photo resist / Cover film(PP) FLASH POINT : N.A.(gelation) VAPOR DENSITY : N.E. ODOR : Mild odor		

SECTION 10 STABILITY AND REACTIVITY : Stable STABILITY CONDITIONS TO AVOID : Heat and sunlight. MATERIALS TO AVOID : Strong acids, strong bases, peroxides and strong oxidizing agents. HAZARDOUS DECOMPOSITION PRODUCTS : Burning may release oxides of carbon, nitrogen, sulphur and other toxic gases or vapors. SECTION 11 TOXICOLOGICAL INFORMATION PRIMARY ROUTE(S) OF ENTRY DERMAL ■ INHALATION □ INGESTION TOXICITY STUDIES : Toxicity studies have not been carried out on this product. Toxicity information available for the ingredients listed in section 2 is given below. HEALTH HAZARDS ACUTE INGESTION TOXICITY : N.E. ACUTE SKIN IRRITATION : Slightly irritant : Epoxy resin(MW ≤ 700 , Carc.cat.3;R40,R43) MUTAGENICITY is suspected to have a mutagenicity CARCINOGENICITY □ NTP 🗆 IARC 🗆 OSHA ■ NOT LISTED SYMPTOMS OF OVER EXPOSURE INHALATION : Slight irritation to respiratory tract. Highly concentrated vapor may cause headaches, dizziness, and nausea. : Slight irritation EYES SKIN : Sensitization INGESTION : Expected to have a low order of toxicity. SECTION 12 ECOLOGICAL INFORMATION ACUTE FISH TOXICITY : Ecological data are not available BIODEGRADABILITY : U.K.

SECTION 13

DISPOSAL CONSIDERATIONS

Incineration or landfill in accordance with local regulations.

SECTION 14

TRANSPORT INFORMATION

IMDG-CODE	:	Free
IATA	:	Free
UN	:	Free
FLASH POINT	:	N.A. (gelation)

SECTION 15	REGULATORY INFORMATION	
EEC LABELING	: Xn=Harmful	
RISK PHRASES	 R40 - Limited evidence of a carcinogenic effect. R43 - May cause sensitization by skin contact. R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. 	
SAFETY PHRASES	: S36/37 - Wear suitable protective clothing and gloves. S22 - Do not breathe dust. S61 - Avoid release to the environment. Refer to special instructions/Safety data sheets.	
TSCA	: □ on TSCA □ on LVE ■ NOT LISTED *This product contains a substance listed on the TSCA inventory and in addition is subject to the Significant New Use Rule(SNUR) found in 40CFR721.9664	
EINECS	: □ on EINECS □ on ELINCS ■NOT LISTED	
SECTION 16	OTHER INFORMATION	

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation. The information contained herein is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It should not therefore be construed as guaranteeing specific properties. It may not be valid for this material, if used in combination with any other materials.

Data provided in Section 11,12 and 15 are quoted from raw materials MSDSs.

Please kindly contact to our local sales office/distributor in case if you plan to export this product before use.