

T H P - 1 0 0 D X 1

Updated : November 9, 2015

MSDS No. : MS-00164901-06

## SECTION 1 IDENTIFICATION

MANUFACTURER      TAIYO INK MFG. CO.,LTD.                      TEL 81-493-61-2724  
                          900 Hirasawa, Ranzan-machi, Hiki-gun      FAX 81-493-61-2824  
                          Saitama, 355-0215 JAPAN

DISTRIBUTOR

EMERGENCY CONTACT    TEL 81-493-61-2724                      FAX 81-493-61-2824

## SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS	CAS No.	CONTENTS (%)	OSHA (PEL)	ACGIH (TLV)
Bisphenol A-(epichlorhydrin);Epoxy resin(Mw ≤ 700)	25068-38-6	< 20%	N. A.	N. A.
Epoxy resin(Mw ≤ 700)	Trade secret	< 20%	N. A.	N. A.
Barium Sulfate	7727-43-7	< 3%	dust 15mg/m3	10mg/m3
Silica, fused, respirable dust	Trade secret	< 38%	0.3mg/m3	N. A.
Silica, amorphous	7631-86-9	< 10%	N. A.	dustTLV10mg/m3
Calcium carbonate	471-34-1	< 8%	N. A.	N. A.

## SECTION 3 HAZARDS IDENTIFICATION

INHALATION : Highly concentrated vapor irritates nose, throat and lungs.  
                          May cause headache and dizziness.

EYE CONTACT : Moderately irritation

SKIN CONTACT : Moderately irritation

INGESTION : Harmful, if swallowed.

## SECTION 4 FIRST AID MEASURES

SKIN CONTACT : Wash with plenty of running water using a mild soap. Do not use  
                          organic solvents.

EYE CONTACT : Rinse immediately with clean water for at least 15 minutes.  
                          If irritation persists, seek medical attention.

INHALATION : Immediately carry the victim to a place where fresh air is available.  
                          If irritation persists, treat with oxygen and seek medical attention.

INGESTION : Obtain medical advice immediately. It is not recommended that  
                          vomiting be induced except on medical advice.

## SECTION 5

## FIRE-FIGHTING MEASURES

---

SUITABLE EXTINGUISHING MEDIA	: Carbon dioxide, foam, powder.
UNSUITABLE EXTINGUISHING MEDIA	: Water spray and water jet.
EXPOSURE HAZARDS	: Burning may release oxides of carbon, nitrogen, sulphur and other toxic gases or vapors. Do not release chemically contaminated water into drains or surface waters. Dispose of contaminated waters and soil according to local regulations.
PROTECTIVE EQUIPMENT FOR FIREFIGHTERS MEASURES	: Use full protective clothing and self-contained breathing apparatus. : Promptly move transferable containers to another safety area. Check the speed and spread of fire. Extinguish the fire with suitable extinguisher from the windward side.

---

## SECTION 6

## ACCIDENTAL RELEASE MEASURES

---

PERSONAL PRECAUTION	: Avoid ignition sources. Avoid contact with skin, eyes and clothing. Avoid inhaling vapor.
ENVIRONMENTAL PRECAUTIONS METHODS FOR CLEANING	: Prevent contamination of soil, drains and surface waters : Scoop up or absorb into combustible material, wipe out a stain in use organic solvents. Dispose in accordance with local regulations.

---

## SECTION 7

## HANDLING AND STORAGE

---

HANDLING	: Handle with care. Avoid ignition sources. Ensure good ventilation and local exhaust. Do not smoke at the workplace.
STORAGE	: Store in the original sealed container at less than 10°C. Avoid direct exposure to UV and sunlights.

---

## SECTION 8

## EXPOSURE CONTROLS/PERSONAL PROTECTION

---

People who know they are chemically sensitive, should avoid contact with this product.	
TECHNICAL PROTECTIVE MEASURES	: No special safety measures required.
EXPOSURE CONTROL LIMITS	: (See PEL and TLV values shown in section 2)
RESPIRATORY PROTECTION	: Wear suitable mask to avoid inhalation of vapor.
HAND PROTECTION	: Wear chemical resistant gloves.
EYE PROTECTION	: Wear safety glasses.
SKIN PROTECTION	: Wear suitable protective working cloths.

---

## SECTION 9

## PHYSICAL AND CHEMICAL PROPERTIES

---

BOILING POINT	: N.E.	COLOR	: Light brown from White
FLASH POINT	: N.A. (gelation)	FORM	: Paste
VAPOR PRESSURE	: N.E.	VAPOR DENSITY	: N.E.
SOLUBILITY IN WATER	: N.E.	ODOR	: Mild odor
		SPECIFIC GRAVITY	: N.E.

\*Data of the organic solvents or monomers contained in this product is quoted.

## SECTION 10

## STABILITY AND REACTIVITY

---

STABILITY : Stable  
CONDITIONS TO AVOID : Heat and sunlight.  
MATERIALS TO AVOID : Strong acids, strong bases, peroxides and strong oxidizing agents.  
HAZARDOUS DECOMPOSITION PRODUCTS : Burning may release oxides of carbon, nitrogen, sulphur and other toxic gases or vapors.

---

## SECTION 11

## TOXICOLOGICAL INFORMATION

## PRIMARY ROUTE(S) OF ENTRY

DERMAL             INHALATION             INGESTION

TOXICITY STUDIES : Toxicity studies have not been carried out on this product. Toxicity information available for the ingredients listed in section 2 is given below.

## HEALTH HAZARDS

ACUTE INGESTION TOXICITY : N.E.  
ACUTE SKIN IRRITATION : Slightly irritant  
MUTAGENICITY : Bisphenol A-(epichlorhydrin); Epoxy resin ( $M_w \leq 700$ )  
Epoxy resin ( $M_w \leq 700$ )  
are suspected to have a mutagenicity

## CARCINOGENICITY

NTP                     IARC                     OSHA                     NOT LISTED

## SYMPTOMS OF OVER EXPOSURE

INHALATION : Slight irritation to respiratory tract. Highly concentrated vapor may cause headaches, dizziness, and nausea.  
EYES : Moderately irritation  
SKIN : Moderately irritation  
INGESTION : Expected to have a low order of toxicity.

---

## SECTION 12

## ECOLOGICAL INFORMATION

---

ACUTE FISH TOXICITY : Ecological data are not available  
BIODEGRADABILITY : U. K.

---

## SECTION 13

## DISPOSAL CONSIDERATIONS

---

Incineration or landfill in accordance with local regulations.

---

## SECTION 14

## TRANSPORT INFORMATION

---

IMDG-CODE : 3082  
IATA : 3082  
CLASS : 9  
FLASH POINT : N. A. (gelation)  
UN : 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N. O. S  
(BIS-A TYPE EPOXY RESIN)  
Paking Group : III  
FLASH POINT : N. A. (gelation)

---

---

SECTION 15REGULATORY INFORMATION

---

EEC LABELING : Xi=Irritant

RISK PHRASES : R36/38 - Irritating to eyes and skin.  
R43 - May cause sensitization by skin contact.  
R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY PHRASES : S37/39 - Wear suitable gloves and eye/face protection.  
S28 - After contact with skin, wash immediately with plenty of water and soap.  
S61 - Avoid release to the environment. Refer to special instructions/Safety data sheets.

TSCA :  on TSCA  on LVE  NOT LISTED  
EINECS :  on EINECS  on ELINCS  NOT LISTED

---

## SECTION 16

OTHER INFORMATION

---

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation. The information contained herein is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It should not therefore be construed as guaranteeing specific properties. It may not be valid for this material, if used in combination with any other materials.

Data provided in Section 11,12 and 15 are quoted from raw materials MSDSs.

Please kindly contact to our local sales office/distributor in case if you plan to export this product before use.